

ITEM NO.	QTY	UNIT	DESCRIPTIONS	TOTAL ABC	BID PRICE PER UNIT	TOTAL BID PRICE
	1	piece	Fusion Machine - • Used to connect PPR, PVC, and PE plastic pipes • Capacity: 20 to 63mm pipes • Dies: 20, 25, 32, 40, 50, and 63mm • 800 Watts • Includes stand, allen key, screwdriver, screws, and carrying case. -			
	1	piece	Pipe Wrench - • Heavy Duty • ½inch – 2inch (1 set) -			
	3	unit	Grass Cutter - 2 stroke Model CG-411, 1450 watts, 7500r/Min, 305mm 40.2cc -			
	2	unit	Ladder - Fiber glass, sure step extension, 14ft-25ft extendable, 150kgs capacity -			
	1	unit	Welding Machine - portable, 220v60kh 60-70 amps rated, input-18Kva cycle-30`kgs -			
	2	unit	Blower - 2 stroke, 0.8hp, 4.4kgs, low noise with high blowing power integrated muffler -			
	4	unit	Wheel Barrow - tray thickness: 0.7mm, handle: 32mm x 1.2mm, sand capacity: 6CBF, wheel: 3.50-8pneumatic -			
	1	unit	Generator - single phase, gasoline reated voltage 230volts/ 60 Hz Output 8Kw, surge 3.4kw 4 gallons fuel tank -			
	1	unit	Jigsaw - • heavy duty • Continuous rating input: 450W • Capacity, in wood at 90°: 65mm (2-9/16inch) • Capacity, in steel at 90°: 6mm (1/4inch) • Length of stroke: 18mm (11/16inch) • No load speed (rpm): 500 - 3,100 • Dimensions (L x W x H): 217mm x 77mm x 197mm (8-1/2inch) x 3inch x 7-3/4inch) • Net weight: 1.8kg (4.0lbs) • Power supply cord: 2.0m (6.6ft) -			
	1	set	Bench Vise - Heavy duty, 8" 150mm with swivel base -			
	1	set	Pressure Washer - Gas powered, 3050 PSI, 2.5 GPM, 25 foot by ¼ inch hose, pneumatic tires and wheel placement. Ergonomic rust resistant wand assembly -			
	1	set	Contactora - Full voltage magnetic contactor with thermal overload, for 4" deep well pump. -			
	1	set	Submersible pump and motor - TECHNICAL DATA Operating range: from 1 to 16 m3 /h, with head up to 10.2 metres. Liquid temperature range: from 0 °C to 35 °C for domestic use. Pumped liquid: dirty water without fibers. Particle size for free passage of solids through the suction grid: NOVA 180 - NOVA 200 5 mm. NOVA 300 - NOVA 600 10 mm. Minimum draught depth: NOVA 180 A 77 mm NOVA 180 NA - NOVA 200 8 mm NOVA 300 85 mm NOVA 600 A 175 mm NOVA 600 NA 38 mm Max. Immersion depth: 7 meters. Maximum dry run time: 1 minute. Protection class: IP 68. Insulation class: F. -			

PURPOSE: For Maintenance and Demolition use c/o CBAO. (Capital Outlay

NOTED:

- 1) Delivery Period within _____ calendar days
- 2) price Validity shall be for a period of _____ calendar days
- 3) Warranty (for equipments) _____ Minimum of 1 year

THIS IS TO CERTIFY THAT THIS RFP WAS
 ISSUED AT THE _____ 7th FLOOR WESTERN
 _____ ROOMS CITY GOVERNMENT W/1
 _____ THREE (3) BONDING AGENTS UP
 POSTING PERIOD: _____
 OPENING OF RFP/BIDS: _____
 POSTED BY: _____

- 4) Bid Price should be inclusive of VAT and delivery charges
- 5) Please indicate the brand of your offer. For machines/equipment, please attach brochure.

Name of Establishment

Philgeps Registry No.

Printed Name and Signature of Bidder

Address and Contact Number

TIN